Crane – P 800 - 7.2 meter

	a=: :	
Part&Accessory	QTY	Pictures
The arm body (Crane Segments 120cm long per section ,3mm thick triangle tube with 13/13/13 cm size)	6x	
Stent	1x	
High quality dutch head (more than 360 degree rotation, the length of 40 cm, The slowest acuities were 0.5 times/min, fastest 10 times or more per minute, low noise)	1x	max loading: 10kg
Dutch head controller DV the controller	1x	W T

7 inch monitor	1x	
Stainless steel standard parts	1x	
Wire rope pull 1. Level of steel wire rope pull 2 sets 2. 1 set of vertical wire rope 3. Head 1 set of wire rope	4x	
Other parts	1x	

Crane – P 800 - 10 meter

<u>Oral</u>		1 000 TO MCCCI
Part&Accessory	QTY	Pictures
The arm body (Crane Segments 120cm long per section ,3mm thick triangle tube with 13/13/13 cm size)	8x	
Stent	1x	
High quality dutch head (more than 360 degree rotation, the length of 40 cm, The slowest acuities were 0.5 times/min, fastest 10 times or more per minute, low noise)	1x	max loading: 20kg
Dutch head controller DV the controller	1x	W T

7 inch monitor	1x	and lot
Stainless steel standard parts	1x	
Wire rope pull 2. Level of steel wire rope pull 2 sets 2. 1 set of vertical wire rope 3. Head 1 set of wire rope	4x	
Other parts	1x	
The packing box	2x	

Crane - P -1500 - 8 meter

Claile - F - 1300 - 6 Metel		
Part&Accessory	QTY	Pictures
The arm body (Crane Segments 100cm long per section ,3mm thick triangle tube with 13/13/13 cm size)	8x	
Stent	1x	
High quality dutch head (more than 360 degree rotation, the length of 40 cm, The slowest acuities were 0.5 times/min, fastest 10 times or more per minute, low noise)	1x	max loading: 20kg

Dutch head controller 1.The power switch 2.220V(Contact us:Voltage can be replaced according to different countries) 3.DC12V 4. Video channel	1x	
Professional & DV the controller	1x	EX1 series special interface 2.5 the DV machine control interface 8 needles broadcasting machine control interface Fuji 12 needle control interface
SLR camera controller	1x	SLR USB interface control *** *** *** *** *** *** ***
10 inch HDMI monitor	1x	

Stainless steel standard parts	1x	
Wire rope pull 3. Level of steel wire rope pull 2 sets 2. 1 set of vertical wire rope 3. Head 1 set of wire rope	4x	
Other parts	1x	
The packing box	2x	

Crane – P- 1200 - 6 meter

Orai		1 1200 0 1110(01
Part&Accessory	QTY	Pictures
The arm body (Crane Segments 100cm long per section ,3mm thick triangle tube with 13/13/13 cm size)	6x	
Stent	1x	
High quality dutch head (more than 360 degree rotation, the length of 40 cm, The slowest acuities were 0.5 times/min, fastest 10 times or more per minute, low noise)	1x	max loading: 20kg
Dutch head controller 3.The power switch 2.220V(Contact us:Voltage can be replaced according to different countries) 3.DC12V 4. Video channel	1x	

Professional & DV the controller	1x	EX1 series special interface 2.5 the DV machine control interface 8 needles broadcasting machine control interface Fuji 12 needle control interface
SLR camera controller	1x	BLR USB interface control 以 は は は は は は は は は は は は は は は は は は
7 inch HDMI monitor	1x	
Stainless steel standard parts	1x	

Wire rope pull 7. Level of steel wire rope pull 2 sets 2. 1 set of vertical wire rope 3. Head 1 set of wire rope	4x	
Other parts	1x	
The packing box	2x	

Crane – P 1500 – 10 meter

Clane		
Part&Accessory	QTY	Pictures
The arm body (Crane Segments 120cm long per section ,3mm thick triangle tube with 15/15/15 cm size)	8x	
Stent	1x	
High quality dutch head (more than 360 degree rotation, the length of 40 cm, The slowest acuities were 0.5 times/min, fastest 10 times or more per minute, low noise)	1x	max loading: 20kg
Dutch head controller	1x	
Professional & DV the controller	1x	EX1 series special interface 2.5 the DV machine control interface 8 needles broadcasting machine control interface Fuji 12 needle control interface

SLR camera controller	1x	LR USB interface control As a sea sea sea sea sea sea sea sea sea
10 inch HDMI monitor	1x	
Control box and the power supply system		
7.The power switch 2.220V(Contact us:Voltage can be replaced according to different countries) 3.DC12V 4. Video channel	1x	
Stainless steel standard parts	1x	
Professional lens servo system (Professional machine can control the IRIS and FOCUS)	1x	
Wire rope pull		
11. Level of steel wire ropepull 2 sets2. 1 set of vertical wire rope3. Head 1 set of wire rope	4x	
Other parts	1x	

Crane – P-1500 – 12 meter

Orane 1 1000 12 meter					
Part&Accessory	QTY	Pictures			
The arm body (Crane Segments 120cm long per section ,3mm thick triangle tube with 15/15/15 cm size)	10x				
Stent	1x				
High quality dutch head (more than 360 degree rotation, the length of 40 cm, The slowest acuities were 0.5 times/min, fastest 10 times or more per minute, low noise)	1x	max loading: 20kg			
Dutch head controller	1x				
Professional & DV the controller	1x	EX1 series special interface 2.5 the DV machine control interface 8 needles broadcasting mechine control interface Fuji 12 needle control interface			

SLR camera controller	1x	SLR USB interface control Representation of the control of the co
10 inch HDMI monitor	1x	
Control box and the power supply system		1 1 1 7
8.The power switch 2.220V(Contact us:Voltage can be replaced according to different countries) 3.DC12V 4. Video channel	1x	
Stainless steel standard parts	1x	
Professional lens servo system (Professional machine can control the IRIS and FOCUS)	1x	
Wire rope pull		
12. Level of steel wire rope pull 2 sets 2. 1 set of vertical wire rope 3. Head 1 set of wire rope	4x	
Other parts	1x	

Crane - P-1500 – 15 meter

Ofan	С	-1300 - 13 Meter
Part&Accessory	QTY	Pictures
The arm body (Crane Segments 150cm long per section ,3mm thick triangle tube with 15/15/15 cm size)	10x	
Stent	1x	
High quality dutch head 3 axis (more than 360 degree rotation, the length of 40 cm, The slowest acuities were 0.5 times/min, fastest 10 times or more per minute, low noise)	1x	max loading: 20kg
Dutch head controller	1x	
Professional & DV the controller	1x	EX1 series special interface 2.5 the DV machine control interface 8 needles broadcasting machine control interface Fuji 12 needle control interface

SLR camera controller	1x	SLR USB interface control
10 inch HDMI monitor	1x	
Control box and the power supply system		
12.The power switch 2.220V(Contact us:Voltage can be replaced according to different countries) 3.DC12V 4、Video channel	1x	
Stainless steel standard parts	1x	
Professional lens servo system (Professional machine can control the IRIS and FOCUS)	1x	
Wire rope pull		
16. Level of steel wire rope pull 2 sets 2. 1 set of vertical wire rope 3. Head 1 set of wire rope	4x	
Other parts	1x	
The packing box	3x	

Crane – P -1500 – 18 meter

		-1300 – 18 Meter
Part&Accessory	QTY	Pictures
The arm body (Crane Segments 150cm long per section ,3mm thick triangle tube with 15/15/15 cm size)	12x	
Stent	1x	
High quality dutch head 3 axis (more than 360 degree rotation,the length of 40 cm,The slowest acuities were 0.5 times/min, fastest 10 times or more per minute,low noise)	1x	max loading: 20kg
Dutch head controller	1x	
Professional & DV the controller	1x	EX1 series special interface 2.5 the DV machine control interface 8 needles broadcasting machine control interface Fuji 12 needle control interface

SLR camera controller	1x	SLR USB interface control Interface control
10 inch HDMI monitor	1x	
Control box and the power supply system		1 1 1 1
13.The power switch 2.220V(Contact us:Voltage can be replaced according to different countries) 3.DC12V 4. Video channel	1x	
Stainless steel standard parts	1x	
Professional lens servo system (Professional machine can control the IRIS and FOCUS)	1x	
Wire rope pull		
17. Level of steel wire ropepull 2 sets2. 1 set of vertical wire rope3. Head 1 set of wire rope	4x	
Other parts	1x	
The packing box	3x	